

## Productinformatieblad

Uitgave 02.2014

Geotex

## Geotex

NF 6 - 60S 60G/M<sup>2</sup>

<b>KENMERKEN</b> <i>(Characteristics)</i>	<b>NORMWAARDE/TOLERANTIE</b> <i>(Specified Value/Tolerance)</i>	<b>TESTNORM<sup>1</sup></b> <i>(Test Standard<sup>1</sup>)</i>
Materiaal <i>Material</i>	60 g/m <sup>2</sup> PES/PP Vlies <i>60 g/m<sup>2</sup> non-woven PES/PP fabric</i>	
Dikte <i>thickness</i>	35 mm +/- 0,15	Handtaster
Oppervlaktegewicht <i>weight</i>	60 g/m <sup>2</sup> +/- 20	DIN EN 29073-1
Max. Treksterkte N/5cm - Lengterichting <i>tensile strenght N/5cm - along</i>	> 85 N	DIN EN 29073-3
Max. Treksterkte N/5cm - Dwarsrichting <i>tensile strenght N/5cm - accross</i>	> 100 N	DIN EN 29073-3
Maximale Uitrekking % - Lengterichting <i>elongation % - along</i>	> 50 %	
Maximale Uitrekking % - Dwarsrichting <i>elongation % - across</i>	> 70 %	
Breedte in cm <i>width</i>	10 - max 100 cm.	
Luchtdoorlaatbaarheid <i>air permeability</i>	> 1500 l/h (A = 20 cm <sup>2</sup> )	

<sup>1</sup> Conform  
<sup>1</sup> according to